

SAFETY DATA SHEET

AMSOIL Passenger Car & Light Truck Antifreeze & Coolant

According to Appendix D, OSHA Hazard Communication Standard 29 CFR §1910.1200 and WHMIS 2015, in compliance with the Hazardous Product Act (HPA, as amended) and the requirements of the Hazardous Product Regulations (HPR).

1. Identification

Product identifier

Product name

AMSOIL Passenger Car & Light Truck Antifreeze & Coolant

Product number ANTPC

Recommended use of the chemical and restrictions on use

Application Coolant.

Uses advised against Avoid the formation of mists.

Details of the supplier of the safety data sheet

Supplier AMSOIL INC.

Bordner, Ladner, Gervais Scotia Plaza, 40 King St W Toronto, ON, Canada M5H 3Y4

T: +1 416-367-6547

Manufacturer AMSOIL INC.

One AMSOIL Center, Superior, WI 54880, USA. T: +1 715-392-7101 compliance@amsoil.com

Emergency telephone number

Emergency telephone CHEMTREC: Within USA and Canada: 1-800-424-9300

Outside the USA and Canada: +1 703-741-5970

(collect calls accepted) 24/7

2. Hazard(s) identification

Classification of the substance or mixture

OSHA/WHMIS Regulatory

This Product is Hazardous under the OSHA Hazard Communication Standard and according

to the hazard criteria of the Hazardous Product Regulations.

Physical hazards Not Classified

Health hazards Acute Tox. 4 - H302 Skin Irrit. 2 - H315 Eye Irrit. 2A - H319 STOT RE 2 - H373

Environmental hazards Not Classified

Label elements

Pictogram

Status





Signal word Warning

AMSOIL Passenger Car & Light Truck Antifreeze & Coolant

Hazard statements H302 Harmful if swallowed.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements P260 Do not breathe vapor/ spray.

P264 Wash contaminated skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P280 Wear protective gloves, eye and face protection.

P301+P312 If swallowed: Call a poison center/ doctor if you feel unwell.

P302+P352 If on skin: Wash with plenty of water.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing. P314 Get medical advice/ attention if you feel unwell.

P330 Rinse mouth.

P332+P313 If skin irritation occurs: Get medical advice/ attention.
P337+P313 If eye irritation persists: Get medical advice/ attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P501 Dispose of contents/ container in accordance with national regulations.

Contains Ethanediol, Sodium 4(or 5)-methyl-1H-benzotriazolide

Other hazards

This product does not contain any substances classified as PBT or vPvB.

3. Composition/information on ingredients

Mixtures

Ethanediol 25 - <50%

CAS number: 107-21-1

Classification

Acute Tox. 4 - H302 STOT RE 2 - H373

Potassium succinate 2.5 - <3%

CAS number: 676-47-1

Classification

Skin Irrit. 2 - H315 Eye Irrit. 2A - H319

Dodecanedioic acid 1 - <2.5%

CAS number: 693-23-2

Classification

Eye Irrit. 2A - H319



AMSOIL Passenger Car & Light Truck Antifreeze & Coolant

Sodium 4(or 5)-methyl-1H-benzotriazolide

1 - < 2.5%

CAS number: 64665-57-2

Classification

Acute Tox. 4 - H302 Skin Corr. 1B - H314 Eye Dam. 1 - H318 Aquatic Chronic 2 - H411

The full text for all hazard statements is displayed in Section 16.

Composition comments The exact percentage is withheld as a trade secret in accordance with 29 CFR 1910.1200.

4. First-aid measures

Description of first aid measures

General information Get medical attention immediately. Show this Safety Data Sheet to the medical personnel.

Inhalation Remove affected person from source of contamination. Move affected person to fresh air and

keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Place unconscious person on

their side in the recovery position and ensure breathing can take place.

Ingestion Rinse mouth thoroughly with water. Remove any dentures. Give a few small glasses of water

or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Place unconscious person on their side in the recovery position and ensure breathing can take place. Maintain an open airway. Loosen tight clothing

such as collar, tie or belt.

Skin Contact Rinse with water.

Eye contact Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide

apart. Continue to rinse for at least 10 minutes.

Protection of first aiders First aid personnel should wear appropriate protective equipment during any rescue. Wash

contaminated clothing thoroughly with water before removing it from the affected person, or wear gloves. It may be dangerous for first aid personnel to carry out mouth-to-mouth

resuscitation.

Most important symptoms and effects, both acute and delayed

General information See Section 11 for additional information on health hazards. The severity of the symptoms

described will vary dependent on the concentration and the length of exposure.

Inhalation Prolonged inhalation of high concentrations may damage respiratory system.

Ingestion May cause discomfort if swallowed. Stomach pain. Nausea, vomiting.

Skin contact Redness. Irritating to skin.

Eye contact Irritating to eyes.

Indication of immediate medical attention and special treatment needed

5. Fire-fighting measures

AMSOIL Passenger Car & Light Truck Antifreeze & Coolant

Extinguishing media

Suitable extinguishing media Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-

extinguishing media suitable for the surrounding fire.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

Special hazards arising from the substance or mixture

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up.

This product is toxic.

Hazardous combustion

products

Hydrocarbons. Carbon monoxide (CO). Carbon dioxide (CO2). Aldehydes. Alcohols. Ethers.

Advice for firefighters

Protective actions during

firefighting

Avoid breathing fire gases or vapors. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapors and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.

Special protective equipment

for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Standard Firefighter's clothing including helmets, protective boots and gloves will provide a basic level of protection for chemical incidents.

6. Accidental release measures

Personal precautions

Personal precautions, protective equipment and emergency procedures

No action shall be taken without appropriate training or involving any personal risk. Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Wash thoroughly after dealing with a spillage. Ensure procedures and training for emergency decontamination and disposal are in place. Do not touch or walk into spilled material. Avoid contact with skin and eyes. Use protective equipment appropriate for surrounding materials.

Environmental precautions

Environmental precautions Aquatic toxicity is unlikely to occur. However, large or frequent spills may have hazardous

effects on the environment. Absorb spillage with non-combustible, absorbent material. Large Spillages: Inform the relevant authorities if environmental pollution occurs (sewers,

waterways, soil or air).

Methods and material for containment and cleaning up

Methods for cleaning up

Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Small Spillages: Absorb spillage with sand or other inert absorbent. Collect and place in suitable waste disposal containers and seal securely. Large Spillages: If leakage cannot be stopped, evacuate area. Flush spilled material into an effluent treatment plant, or proceed as follows. Contain and absorb spillage with sand, earth or other non-combustible material. Place waste in labeled, sealed containers. Clean contaminated objects and areas thoroughly, observing environmental regulations. The contaminated absorbent may pose the same hazard as the spilled material. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

AMSOIL Passenger Car & Light Truck Antifreeze & Coolant

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health

hazards. See Section 12 for additional information on ecological hazards. For waste disposal,

see Section 13.

7. Handling and storage

Precautions for safe handling

Usage precautions Read and follow manufacturer's recommendations. Wear protective clothing as described in

Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Handle all packages and containers carefully to minimize spills. Keep container tightly sealed when not in use. Avoid the formation of mists. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment. Do

not reuse empty containers. Avoid contact with used product.

the toilet. Change work clothing daily before leaving workplace.

Advice on general occupational hygiene

Wash promptly if skin becomes contaminated. Take off contaminated clothing and wash before reuse. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using

Storage precautions Store away from incompatible materials (see Section 10). Store in accordance with local

regulations. Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage. Utilize retaining walls to prevent soil and water pollution in the event of spillage. The storage area floor should

be leak-tight, jointless and not absorbent.

Storage class Chemical storage.

Conditions for safe storage, including any incompatibilities

Specific end uses(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.

8. Exposure Controls/personal protection

Control parameters

Occupational exposure limits

Comments

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Ethanediol

Ceiling exposure limit: ACGIH 100 mg/m³ Aerosol

A4

ACGIH = American Conference of Governmental Industrial Hygienists.

A4 = Not Classifiable as a Human Carcinogen.

Exposure controls

Appropriate engineering controls

Provide adequate ventilation. Personal, workplace environment or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Use process enclosures, local exhaust ventilation or other engineering controls as the primary means to minimize worker exposure. Personal protective equipment should only be used if worker exposure cannot be controlled adequately by the engineering control measures. Ensure control measures are regularly inspected and maintained. Ensure operatives are trained to minimize exposure.

AMSOIL Passenger Car & Light Truck Antifreeze & Coolant

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with OSHA 1910.133 and/or the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.6), and any relevant provincial regulation relating to health and safety at work. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with OSHA 1910.138 and/or the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.9), and be demonstrated to be impervious to the chemical and resist degradation. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended.

Other skin and body protection

Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.

Hygiene measures

Provide eyewash station and safety shower. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Clean equipment and the work area every day. Good personal hygiene procedures should be implemented. Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke. Preventive industrial medical examinations should be carried out. Warn cleaning personnel of any hazardous properties of the product.

Respiratory protection

Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective equipment is suitable for its intended use and is NIOSH approved. Check that the respirator fits tightly and the filter is changed regularly. Full face mask respirators with replaceable filter cartridges should comply with OSHA 1910.134 and/or the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.7), and any relevant provincial regulation relating to health and safety at work. Gas and combination filter cartridges should comply with OSHA 1910.134 and/or the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.7), and any relevant provincial regulation relating to health and safety at work. Half mask and quarter mask respirators with replaceable filter cartridges should comply with OSHA 1910.134 and/or the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.7), and any relevant provincial regulation relating to health and safety at work.

Environmental exposure controls

Keep container tightly sealed when not in use.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance Liquid.

Color Yellow.

Odor Sweetish.

Odor threshold Not available.

pH pH (concentrated solution): 8.0 - 8.6

Melting point -34°F

Initial boiling point and range 226°F

Flash point 116°C/241°F Aqueous solution.

AMSOIL Passenger Car & Light Truck Antifreeze & Coolant

Evaporation rate

Upper/lower flammability or

explosive limits

Not available.

Vapor pressure

10 mm Hg @ 20°C/68°F Component data.

Vapor density

2.1 Component data.

Relative density

1.03 - 1.08 @ 60°F

Solubility(ies)

Soluble in water.

Partition coefficient

Not available.

Auto-ignition temperature

Not available.

Decomposition Temperature

Not available.

Viscosity

Not applicable.

Explosive properties

Not considered to be explosive.

Oxidizing properties

Does not meet the criteria for classification as oxidizing.

Other information

No information required.

10. Stability and reactivity

Reactivity

See the other subsections of this section for further details.

Stability

Stable at normal ambient temperatures and when used as recommended. Stable under the

prescribed storage conditions.

Possibility of hazardous

reactions

No potentially hazardous reactions known.

Conditions to avoid

There are no known conditions that are likely to result in a hazardous situation.

Materials to avoid

Oxidizing agents. Acids - oxidizing. Strong acids. Strong alkalis.

Hazardous decomposition

products

Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors.

Aldehydes. Alcohols. Ethers.

11. Toxicological information

Information on toxicological effects

Acute toxicity - oral

Notes (oral LD₅₀) Acute Tox. 4 - H302 Harmful if swallowed.

ATE oral (mg/kg) 1,226.05

Acute toxicity - dermal

Notes (dermal LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Based on available data the classification criteria are not met.

Skin corrosion/irritation

Animal data Irritating.

AMSOIL Passenger Car & Light Truck Antifreeze & Coolant

Serious eye damage/irritation

Serious eye damage/irritation Causes serious eye irritation.

Respiratory sensitization

Respiratory sensitization Based on available data the classification criteria are not met.

Skin sensitization

Skin sensitizationBased on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitroBased on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

IARC carcinogenicity

None of the ingredients are listed or exempt.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Reproductive toxicity -

development

Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposureNot classified as a specific target organ toxicant after a single exposure.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure STOT RE 2 - H373 May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

Inhalation Prolonged inhalation of high concentrations may damage respiratory system.

Ingestion May cause discomfort if swallowed. Stomach pain. Nausea, vomiting.

Skin Contact Redness. Irritating to skin.

Eye contact Irritating to eyes.

Route of exposure Ingestion Inhalation Skin and/or eye contact

Target Organs No specific target organs known.

Medical considerations Skin disorders and allergies.

Toxicological information on ingredients.

Ethanediol

Acute toxicity - oral

Notes (oral LD₅₀) Harmful if swallowed.

ATE oral (mg/kg) 500.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ 3,501.0

mg/kg)

AMSOIL Passenger Car & Light Truck Antifreeze & Coolant

Species Mouse

ATE dermal (mg/kg) 3,501.0

Acute toxicity - inhalation

Notes (inhalation LC₅₀) LC₅₀ >2.5 mg/l, Inhalation, Aerosol., Rat 4 hours

Skin corrosion/irritation

Animal data Dose: 0.5 mL, 20 hours, Rabbit Primary dermal irritation index: 0

Skin sensitization

Skin sensitization Guinea pig maximization test (GPMT) - Guinea pig: Not sensitizing.

Germ cell mutagenicity

Genotoxicity - in vitroGene mutation: Negative.

Genotoxicity - in vivoChromosome aberration: Negative.

Carcinogenicity

Carcinogenicity NOAEL 1500 mg/kg/day, Oral, Mouse

Reproductive toxicity

Reproductive toxicity -

fertility

Fertility - NOAEL 1000 mg/kg/day, Oral, Mouse F1

Reproductive toxicity -

development

Developmental toxicity: - NOAEC: 150 mg/m³, Inhalation, Mouse

Specific target organ toxicity - repeated exposure

STOT - repeated exposure STOT RE 2 - H373 May cause damage to organs through prolonged or repeated

exposure.

Target organs Kidneys

12. Ecological Information

Ecotoxicity Not regarded as dangerous for the environment. However, large or frequent spills may have

hazardous effects on the environment.

Toxicity Based on available data the classification criteria are not met.

Ecological information on ingredients.

Ethanediol

Toxicity Aquatic toxicity is unlikely to occur. Based on available data the classification

criteria are not met.

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 72860 mg/l, Pimephales promelas (Fat-head Minnow)

Acute toxicity - aquatic

invertebrates

EC₅₀, 48 hours: >100 mg/l, Daphnia magna

Acute toxicity - aquatic

plants

EC₅₀, 96 hours: >6500 mg/l, Selenastrum capricornutum

Persistence and degradability

AMSOIL Passenger Car & Light Truck Antifreeze & Coolant

Persistence and degradability The degradability of the product is not known.

Ecological information on ingredients.

Ethanediol

Persistence and

The product is readily biodegradable.

degradability

Phototransformation Water - DT₅₀: 46.3 hours

Biodegradation Water - Degradation >90%: 10 days

Bioaccumulative potential

Bio-Accumulative Potential No data available on bioaccumulation.

Partition coefficient Not available.

Ecological information on ingredients.

Ethanediol

Bio-Accumulative Potential No data available on bioaccumulation.

Partition coefficient log Pow: -1.93

Mobility in soil

Mobility No data available.

Ecological information on ingredients.

Ethanediol

Mobility The product is miscible with water and may spread in water systems.

Adsorption/desorption

coefficient

Water - log Koc: 0 @ °C Estimated value.

Henry's law constant 0.1327 Pa m³/mol @ 25°C Estimated value.

Other adverse effects

Other adverse effects None known.

13. Disposal considerations

Waste treatment methods

General information The generation of waste should be minimized or avoided wherever possible. Reuse or recycle

products wherever possible. This material and its container must be disposed of in a safe way. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners

may retain some product residues and hence be potentially hazardous.

Disposal methods Do not empty into drains. Dispose of surplus products and those that cannot be recycled via a

licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labeled with their contents. Incineration or landfill should only be considered when recycling is

not feasible.

AMSOIL Passenger Car & Light Truck Antifreeze & Coolant

14. Transport information

General The product is not covered by international regulations on the transport of dangerous goods

(IMDG, IATA, DOT, TDG).

UN Number

Not applicable.

UN proper shipping name

Not applicable.

Transport hazard class(es)

Transport labels

No transport warning sign required.

Packing group

Not applicable.

Environmental hazards

Environmentally Hazardous Substance

No.

Special precautions for user

Not applicable.

DOT TIH Zone Not applicable.

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

15. Regulatory information

Regulatory References OSHA Hazard Communication Standard 29 CFR §1910.1200 Hazardous Products Regulation

(SOR/2015-17) Transportation of Dangerous Goods Regulations -SOR/2015-100.

US Federal Regulations

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities

None of the ingredients are listed or exempt.

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

The following ingredients are listed or exempt:

Acetaldehyde

Final CERCLA RQ: 1000(454) pounds (Kilograms)

1,4-dioxane

Final CERCLA RQ: 100(45.4) pounds (Kilograms)

Ethanediol

Final CERCLA RQ: 5000(2270) pounds (Kilograms)

SARA Extremely Hazardous Substances EPCRA Reportable Quantities

None of the ingredients are listed or exempt.

SARA 313 Emission Reporting

The following ingredients are listed or exempt:

AMSOIL Passenger Car & Light Truck Antifreeze & Coolant

Acetaldehyde

0.1 %

1.4-dioxane

0.1 %

Ethanediol

1.0 %

CAA Accidental Release Prevention

The following ingredients are listed or exempt:

Acetaldehyde

Threshold Quantity: 10000 lbs

SARA (311/312) Hazard Categories

None of the ingredients are listed or exempt.

OSHA Highly Hazardous Chemicals

The following ingredients are listed or exempt:

Acetaldehyde

Threshold Quantity: 2500 lbs

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins

The following ingredients are listed or exempt:

Acetaldehyde

Known to the State of California to cause cancer.

1,4-dioxane

Known to the State of California to cause cancer.

Ethanediol

Known to the State of California to cause developmental and reproductive toxicity.

California Air Toxics "Hot Spots" (A-I)

The following ingredients are listed or exempt:

Acetaldehyde

1.4-dioxane

Ethanediol

California Air Toxics "Hot Spots" (A-II)

None of the ingredients are listed or exempt.

California Directors List of Hazardous Substances

The following ingredients are listed or exempt:

Acetaldehyde

Ethanol

1,4-dioxane

Ethanediol

Massachusetts "Right To Know" List

The following ingredients are listed or exempt:

Acetaldehyde

Ethanol

AMSOIL Passenger Car & Light Truck Antifreeze & Coolant

1,4-dioxane

Ethanediol

Rhode Island "Right To Know" List

The following ingredients are listed or exempt:

Acetaldehyde

Ethanol

1.4-dioxane

Ethanediol

Minnesota "Right To Know" List

The following ingredients are listed or exempt:

Acetaldehyde

Ethanol

1,4-dioxane

Ethanediol

New Jersey "Right To Know" List

The following ingredients are listed or exempt:

Acetaldehyde

Ethanol

1,4-dioxane

Ethanediol

Pennsylvania "Right To Know" List

The following ingredients are listed or exempt:

Acetaldehyde

Ethanol

1,4-dioxane

Ethanediol

Inventories

Canada - DSL/NDSL

All the ingredients are listed or exempt.

US - TSCA

All the ingredients are listed or exempt.

US - TSCA 12(b) Export Notification

The following ingredients are listed or exempt:

Acetaldehyde

16. Other information



AMSOIL Passenger Car & Light Truck Antifreeze & Coolant

Abbreviations and acronyms used in the safety data sheet

C.A.S. = Chemical Abstracts Service; E.C. No = European Commission number; GHS = Globally Harmonised System; OSHA = Occupational Safety and Health Administration; WHMIS = Workplace Hazardous Materials Information System; DOT = Department of Transport; TDG = Transport of Dangerous Goods Regulations; IMDG = International Maritime

Dangerous Goods; IATA = International Air Transport Association; SARA = Superfund Amendments and Reauthorization Act; CERCLA = Comprehensive Environmental; EPCRA = Emergency Planning and Community Right-to-Know Act; TSCA = Toxic Substances Control

Act; LD/LC/EC = Lethal Dose,Lethal Concentration/Effect Concentration for 50% of population; NOEC = No Overall Effect Concentration; NOEL = No Overall Effect Level; REACH = Registration, Evaluation, Authorisation & Restriction of Chemicals; STOT-RE = Single Target Organ Toxicity - Repeat Exposure; STOT-SE= Specific Target Organ Toxicity - Single Exposure; PBT = Persistent, Bioaccumulative, Toxic; vPvB = Very Persistent, Very

Bioaccumulative.

Classification abbreviations

and acronyms

Acute Tox. = Acute toxicity
Eye Irrit. = Eye irritation
Skin Irrit. = Skin irritation

STOT RE = Specific target organ toxicity-repeated exposure

Key literature references and

sources for data

Source: European Chemicals Agency, http://echa.europa.eu/

Training advice Read and follow manufacturer's recommendations. Only trained personnel should use this

material.

Revision comments This is the first issue.

Revision date 5/18/2018

SDS No. 7610

Hazard statements in full H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H318 Causes serious eye damage. H319 Causes serious eye irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.